


ICS IE ToughCat 7

S/FTP Installation Cable for tougher environments



Application

Generic Data transmission. This cable is a **Cat7 S/FTP** cable meant for use as installation/horizontal cable in tougher electrical and mechanical environment, including ships and offshore units.

Standards

EN 50173-1; EN 50288-4-1
 ISO/IEC 11801; IEC 61156-5
 Det Norske Veritas (DNV) spesifcation No. 6-827.50-2

Fire rating

LSHF-FR(SHF1) : IEC 60754-2; IEC 61034, IEC 60332-3-24

Chemical resistance

Mineral oils IRM 902 (IEC60811-2-1) : 7 days/23°C, 4 hours/70°C
 Diesel - IRM 903 (IEC60811-2-1) : 7 days/23°C, 4 hours/70°C

Certification

This cable is certified by: Det Norske Veritas (DNV) and American Bureau of Shipping (ABS)

Construction

Conductor	Stranded copper wire Ø 0.27 mm ²
Insulation	PE, Ø 1.6 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs
Pair screen	Al-laminated plastic foil around each pair
Overall screen	Copper braid, tinned Ø 6,6 mm
Sheath	Oil resistant, Fire retardant and halogen free LSHF-FR (SHF1).

Mechanical Properties

Bending radius	Without load	8 x D
	With load	4 x D
Temperature range	During operation	-40°C to + 85°C
	During installation	-15°C to + 50°C
Fire load	4 pair	670 MJ/km
Maximum tensile load	During operation	No load
	During installation	100 N

ICS IE ToughCat 7

Electrical Properties

at 20°C

DC loop resistance		≤ 138 Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 5000 MΩxkm
Capacitance	at 800 Hz	Nom. 43 nF/km
Capacitance unbalance	(pair to ground)	≤ 1500 pF/km
Mean Characteristic impedance	@ 100 MHz)	100 ± 5 Ω
Nominal velocity of propagation		0,76c
Propagation delay		≤ 450 ns/100 m
Delay skew		≤ 15 ns/100 m
Transfer impedance	at 1 MHz	≤ 10 mΩ /m
	at 10 MHz	≤ 8 mΩ /m
	at 30 MHz	≤ 10 mΩ /m
Coupling attenuation		≥ 85 dB

Nominal Transmission characteristics

at 20°C

F (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR (dB/100m)	Return loss (dB)	PS-NEXT (dB)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)
1	2,0	90	88		87	85	85	82
4	3,6	90	86	27	87	83	85	82
10	5,5	90	84	30	87	81	79	76
16	7,5	90	82	30	87	79	75	72
20	7,7	90	82	30	87	79	73	70
31.25	9,8	90	80	30	87	77	69	66
62.50	14,0	86	72	30	83	69	63	60
100	17,9	83	65	30	80	62	59	56
155.00	22,4	81	59	26	78	55	57	54
200.00	25,6	78	52	25	75	49	53	50
250.00	28,8	77	48	25	74	45	51	48
300.00	31,6	73	41	23	70	38	47	44
600.00	45,7	71	25	20	68	22	44	41

Technical data

Part no.	Description	Colour	Outer diameter mm	Fire load		Weight kg/km
				MJ/km	kWh/m	
1016274	ToughCat C7 LSHF-FR 4x2/0.27mm2	Grey RAL7035	8,1	670	0,186	75

Product Code Table

Product Description	Product Code	PG Reference Code	PG Part Number
ToughCat C7 LSHF-FR 4x2/0.27mm2	1016274	60011617	60011617
ToughCat C7 LSHF-FR 4x2/0.27mm2 500DP	1016274-00500DP	60011617	60015820
ToughCat C7 LSHF-FR 4x2/0.27mm2 1000DP		60011617	60030363

ICS IE ToughCat 7



All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.