


H01 N2-D (flexible) welding cable



RoHS

CROSS SECTION



Acc. to DIN EN 50525-2-21
(VDE 0285-525-2-21):2012-01

SPECIAL FEATURES

Sheath colour
Black



APPLICATION

For welding specialists with high robustness and flexibility requirements. This special cable is used to transmit high currents from electrical welding devices to welding tools. It is suitable for flexible use under extreme conditions, on assembly lines and handling systems, in machine tool construction, automotive manufacturing and shipbuilding and for manual and automatic arc and spot welding devices. The cable remains highly flexible even under the influence of light, ozone, inert gas, oil and oxygen. It is also resistant to high thermal loads.

STRUCTURE

Conductor	Copper conductor, bare, flexible (class 5) according to DIN VDE 0295 and IEC 60228 cl. 5, HD 383
Cores	Rubber compound insulation
Outer sheath	Cross-linked elastomer with high mechanical strength

TECHNICAL DATA

Nominal voltage	100 V/100 V
Test voltage	1000 V
Operating temperature	-25°C to +60°C
Max. operating temperature	+85°C
Min. installation temperature	-25°C
Max. installation temperature	+80°C
Min. bending radius:	12 x cable diameter

TESTS ACCORDING TO DIN VDE 0472 AND IEC:

Flammability	Test method B according to VDE 0472 part 804 and IEC 332-1
Welding resistance	Test for resistance against welding spatter: according to HD 22.2
Oil resistance	At 100°C, testing temperature 200°C/24h: test method A according to VDE 0472 part 803

Product description	Cu weight	Outer Ø (mm)	Weight (kg/km)
H01 N2-D 16 mm ²	154.0	11.5	204
H01 N2-D 25 mm ²	240.0	13.0	292
H01 N2-D 35 mm ²	336.0	14.5	388
H01 N2-D 50 mm ²	480.0	17.0	542
H01 N2-D 70 mm ²	672.0	19.0	756
H01 N2-D 95 mm ²	912.0	21.5	976
H01 N2-D 120 mm ²	1152.0	24.0	1221