



Technical Data:

- 360 ° contact of the cable umbrella for improved EMC protection
- Material housing: zinc die casting - nickel -plated
- Contact material: Phosphorbronze
- coating contacts: nickel, gilded 0.5µ
- Catchment: max. 30n (according to IEC 60603-7-5)
- Tensile load: 7.7 kg between socket and Plug
- Operating temperature: -10 ° C up to +60 ° C
- Split cycles: = 750
- Diameter copper conductor: AWG (26/1 ... 22),
- Suitable for POE/POE+
- GHMT components certification

Applications:

As a telecommunications connection module for application Neutral telecommunications cable systems of cabling class 6a or applications up to 10GBase-T. The keystone module fits in all common keystone carrier systems.

Dimensions:

HxBxT 19 x 15 x 36mm

Characteristics:

Cat6_A, Class E_A, bis 10GBase-T shielded, 500MHz
gem. EN 60603-7-51, ISO/IEC 11801

electrical Data:

Contact resistance	<20mΩ
Isolation resistance	>500mΩ
Contact - umbrella	>1000V AC 60Hz 1min
PoE suitability	PoE+ according to IEEE 802.3at
Socket contacts	
Split cycles	>1000
Cutting terminals	
Repeatability	>50

Variants	Dimensions in mm	Article number
e-fairline Keystone Modul Cat.6 _A 1xRJ45	HxBxT 26x17x32mm	1330117111TS